

AIMIX

AIMIX Mobile Cone Crushing Plant



Specification of APY2 Mobile Cone Crushing Plant

Model	APY2-10 10F	APY2-12 10F	APY2-12 14F	APY2-1 10C	APY2-16 0C	APY2-20 0C
Crusher	APF-1010	APF-1210	APF-1214	APC-110 C	APC-160 C	APC-200 C
Vibrating Feeder	APS-1548 Y	APS-1848 Y	APS-1860 Y	APS-184 8Y	APS-186 0Y	APS-216 0Y
Max Feed Size(mm)	250	250	300	160	200	215
Tire Configuration	Parallel double-ax is	Parallel double-ax is	Parallel three-axis	Parallel double-a xis	Parallel three-axi s	Parallel three-axi s

Main Belt Conveyor Model(optional)	B650	B800	B800	B650	B800	B1000
Output Belt Conveyor Model (optional)	B500	B650	B650	B500	B650	B650
Under the Screen Belt Conveyor Model	B650	B800	B800	B650	B800	B1000
Generator Power (kW) (optional)	160	200	250	240	280	320
Capacity(t/h)	50-90	70-130	90-180	50-230	80-390	120-420
Conveying Length(mm)	12500	13300	14500	13800	13800	14500
Conveying Width(mm)	2600	2800	2900	3000	3000	3000
Conveying Height(mm)	3950	4200	4500	4400	4400	4500
Weight (t)	26	34	42	32	37	42